Vigor 2865 Series



The Ideal DSL Router with VPN for Small Business and Remote Working

Premium. Reliable. Affordable.

Datasheet



Product Overview

DrayTek's Vigor 2865 series Multi-WAN Firewall VPN routers are ideal for Superfast VDSL Broadband and Ethernet-based FTTP Fibre Broadband. With Gigabit throughput, Quality of Service, VPN client/server, comprehensive Firewall and Content Filtering controls.

Options for Wi-Fi 6 on 'ax' models, or Wi-Fi 5 'ac' models provide fast & efficient wireless connectivity, while the integrated 4G+ LTE modem on 'Lac' models takes full advantage of mobile broadband. The Vigor 2865 series provides a reliable, flexible, and secure networking solution, that's ideal for Home Offices, Small Business and Satellite Offices.

Key Features & Benefits

VDSL and Ethernet Load Balancer

Connect the Vigor 2865 to Superfast Fibre with the integrated VDSL modem. Use the Ethernet WAN with Cable and Ultrafast FTTP. Load Balance multiple connections to boost performance.

Benefits: Fully utilise Fibre Broadband. High performance DSL & Gigabit CPE with flexible application.

Dual-SIM 4G+ LTE Modem

Ensure ultra-reliable connectivity with integrated highperformance 4G+/LTE Category 6 modem on 'L' models. Handle Mobile network outages with Dual-SIM Failover.

Benefits: Fast and Convenient Mobile Broadband. Provide constant connectivity.

Wi-Fi 6 - AX3000 Performance

Wi-Fi 6 wireless provides gigabit Wi-Fi with reliable throughput. Ideal for time-sensitive video conferencing, low latency gaming and handling 4K Ultra-HD streaming, without buffering.

Benefits: Improved wireless performance. Built with the latest technologies.

Robust SMB VPN Router

Quickly and securely connect remote sites with up to 32 VPN tunnels. Enable remote workers to access resources with DrayTek SSL VPN and OpenVPN support.

Benefits: Securely encrypt network access for remote workers and working from home.

5+1 Gigabit LAN Ports

Link Server, Computers, and Network Attached Storage directly, with up to 6 Gigabit LAN ports. VLANs allow for as many as 8 separate networks, with options for Hotspot Captive Portal.

Benefits: Improve quality of service for private and guest data traffic. Connect more devices.

VigorACS SD-WAN Central Management

Manage the Vigor 2865 remotely and utilise DrayTek's powerful SD-WAN features with the VigorACS 3 management platform. Centrally manage & provision whole networks across multiple sites.

Benefits: Save time and money. Provision, manage and monitor remote sites easily, without on-site IT or dedicated staff.



Compatible with VigorACS Centralised Management Platform



Key Specification

- Multi-WAN Gigabit Performance Router with Load-Balancing & Failover
- Up to 950Mbps Firewall Throughput for Ethernet WAN
- 5+1 Gigabit RJ-45 LAN Ports
- Up to 800Mbps VPN Throughput with IPsec acceleration
- 16 DrayTek SSL VPN or OpenVPN Tunnels
- 4G/LTE with dual-SIMs for second backup telco ('L' models)
- AX3000 Wi-Fi 6 Dual Band Wireless ('ax' models)
- AC1300 11ac 'Wave 2' Dual Band Wireless with Mesh ('ac' models)
- 8 LAN Subnets with VLANs (Port-based / 802.1q)
- SPI Firewall and Content Filtering



Technical Specification (UK Hardware Spec.)

- WAN1: VDSL2 / VDSL2 35b / ADSL2+, RJ-11
- WAN2/LAN Switchable Port: 1x Gigabit Ethernet (1G/100M/10M), RJ-45 LAN Ports: 5x Gigabit Ethernet (1G/100M/10M), RJ-45
- 2x USB 2.0 Ports for 3G/4G Modem, thermometer or Printer or 1x USB 2.0 Port ('L' models)
 2x Removable Wireless antennas (wireless models)

- 2x Removable 4G/LTE Wireless antennas ('L' models)
- Wireless On / Off / WPS button
- Recessed Factory Reset button

Performance

- Router Performance:
 - 100 Mb/s Max Sync Rate with VDSL2
 - 300 Mb/s Max Sync Rate with VDSL2 35b
 - 950 Mb/s NAT Throughput for Ethernet WAN with Hardware Acceleration
 - 1.3Gb/s Total Mult-WAN NAT Throughput
 - 800 Mb/s NAT Throughput per WAN without Hardware Acceleration
- 60,000 NAT Sessions
- VPN Performance:
 - 300 Mb/s IPsec (AES256) VPN Performance
 - 800 Mb/s Hardware Accelerated IPsec VPN Performance 130 Mb/s SSL VPN Performance Max. 32 Concurrent VPN Tunnels

 - Max. 16 Concurrent SSL VPN / OpenVPN Tunnels

WAN Interfaces

- WAN1: VDSL2 / VDSL2 35b / ADSL2+
- WAN2: Gigabit Ethernet WAN3: 2.4GHz Wireless WAN ('ac' models)
- WAN4: 5GHz Wireless WAN ('ac' models)
- WANS: 4G/LTE USB Modem (not included) or Integrated 4G/LTE Category 6 Modem ('L' models only)
 WAN6: 4G/LTE USB Modem (not included)

Internet Connection

- Load Balancing: IP-based, Session-based Hardware Acceleration
- 802.1p/q Multi-VLAN Tagging
- Multi-VLAN/PVC
- 2.4GHz & 5GHz Simultaneous Wireless WAN ('ac' models only)
- WAN Active on Demand: Link Failure, Traffic Threshold Connection Detection: PPP, ARP Detect, Ping Detect WAN Data Budget

- **Dynamic DNS**
- DrayDDNS with automated LetsEncrypt Certificates New!
- Full Feature-set Hardware Acceleration:
 - Hardware Accelerated Quality of Service

 - Multi-WAN Data Budget Traffic Graph & Data Flow Monitor
 - Bandwidth Limit
- IPv4 Connection Types: PPPoE, PPPoA, MPoA, DHCP, Static IP, PPTP/L2TP
- IPv6 Connection Types:
 - DSL & Ethernet: PPP, DHCPv6, Static IPv6, TSPC, AICCU, 6rd, 6in4
 - 4G/LTE Modem & USB 4G/LTE Modem: TSPC, AICCU

VDSL & ADSL Features

- BT Infinity Option 1 & Option 2 Compatible
- Compliant with Openreach SIN 498
- Auto Detection of VDSL and ADSL line modes
- Support for G.INP & Vectoring
- - VDSL Standards:
 TU-T G.993.1 VDSL
 ITU-T G.993.2, G.997.1 VDSL2
 - Band Plan: G.998, G.997
 - Annex A, Annex B, Annex C
 - VDSL2 Profile: 8a, 8b, 8c, 8d, 12a, 12b, 17a, 35b
 - OLR, UPBO, DPBO Supported
 - USO Supported
 - Loop Diagnostic Mode DSL Forum WT-114

ADSL Standards:

- ANSI T1.413 Issue2 ITU-T G.992.1 G.dmt (ADSL) ITU-T G.992.2 G.lite ITU-T G.992.3 ADSL2 ITU-T G.992.5 ADSL2+

ATM Protocols:

- RFC-2684/RFC-1483 Multiple Protocol over AAL5 RFC-2516 PPP over Ethernet RFC-2364 PPP over AAL5

- Support for RFC4638 for MTU up to 1500

Integrated 4G LTE Modem Features ('L' models)

Dual-SIM Failover

- 4G LTE Category 6 Modem with fallback to 3G / GPRS Unlocked to any network (BT, EE, 3, O2, Vodafone, Eircom) 4G LTE Max Data Rates:
- - 300Mbps Downlink (Category 6)

- 500Mbps Downlink (Category 6) 50Mbps Uplink (Category 6) 46 LTE (FDD) Bands: 1, 3, 5, 7, 8, 20, 28, 32 46 LTE (TDD) Bands: 38, 40, 41 36 (WCDMA/HSPA+/UMTS) Bands: 1, 3, 5, 8 2x LTE Antennas included with 1m extension cables
- Per-SIM-Card WAN Data Budget
- 2x Standard-Size SIM-Card Slots
- Removable SIM slot cover
- SMS Inbox Send & Receive SMS text messages SMS Router Commands Status Report, Reboot via text message
- LTE Bridge New!

- Wireless Features ('ac' & 'ax' models)

 AX3000 Wi-Fi 6 wireless ('ax' models):802.11ac 2x2 wireless access point

 802.11ax 2x2 wireless access point

 Compatible with 802.11a/b/g/n/ac wireless

 Dual-band (2.4/5Ghz) simultaneous wireless

 Up to 2400Mbps PHY rate at 160MHz with 5GHz

 - Up to 574Mbps PHY rate at 40MHz with 2.4GHz Channel Bandwidth: 20/40MHz for 2.4GHz, 20/40/80/160MHz for
 - 5GHz OFDMA
 - MU-MIMO
 - Tx Beamforming



Technical Specification (UK Hardware Spec.)

- 1024-QAM AC1300 11ac 'Wave 2' Dual Band Wireless ('ac' models):

 - 802.11ac 2x2 wireless access point 2.4GHz: 2x2 MIMO with 2 dBi Antenna Gain
 - 5GHz: 2x2 MU-MIMO with 4 dBI Antenna Gain

 - Backwards Compatible with 802.11a/b/g/n wireless
 Dual-band (2.4/5Ghz) simultaneous wireless
 Up to 866Mbps PHY rate at 80MHz with 5GHz
 Up to 400Mbps PHY rate at 40MHz with 2.4GHz (256-QAM)
 Channel Bandwidth: 20/40MHz for 2.4GHz, 20/40/80MHz for
 - MU-MIMO
- Tx Beamforming
- Mesh Root support with DrayTek VigorAP Mesh Nodes New! (requires f/w 4.3.0)
- Up to 4 SSIDs per radio band
- Extended 5Ghz Band Channels 36-48, 52-64, 100-140
- Wireless Optimisation: Airtime Fairness, AP-Assisted Mobility, Band
- Bandwidth Management (Per Station / Per SSID)

- WMM (Wireless MultiMedia)
 WPS WiFi Protected Setup
 Station Control Time limited wireless connectivity per Station (e.g. 1
- EAPOL Key Retry Disable EAPOL Key Retry to protect unpatched WLAN clients from KRACK
- Wireless Security:
 - WPA2

 - WFA3 New! (requires f/w 4.3.0) Pre-Shared Key authentication Enterprise 802.1x authentication

 - WEP/WPA for Legacy Clients Access Control Blacklist / Whitelist client MAC addresses per

Antenna Specifications (wireless & 'L' models)

- Wireless Antennas (wireless 'ac' models):
 - 2x External Dipole
 - 5GHz Gain: 4 dBi

 - 2.4GHz Gain: 2 dBi
 RP-SMA fitting antenna connectors
 Wireless Antennas (wireless 'ax' models):
 2x External Dipole
- - 5GHz Gain: 4.5 dBi

 - 2.4GHz Gain: 5 dBi
 - RP-SMA fitting antenna connectors
- LTE Antennas ('L' models):

 - 2x External Dipole 2x 1m extension base included
 - Gain: 3 dBi
 - SMA fitting antenna connectors

Firewall & Content Filtering

- IP-based or User-based Firewall Policy User-based Time Quota DoS Attack Defence

- Spoofing Defence
 Content Filtering:
 Application Content Filter
 - URL Content Filter
 - DNS Keyword Filter Web Features

 - Web Category Filter (requires GlobalView subscription)

- Features NAT Port Redirection
- Open Ports
- Port Triggering
- ALG (Application Layer Gateway): SIP, RTSP, FTP, H.323 VPN Pass-Through: PPTP, L2TP, IPsec

- 802.1q Tag-based, Port-based VLAN
- Up to 8 LAN Subnets (NAT or Routing mode selectable per LAN interface)

- Up to 16 VLANs DMZ Port
- DHCP Server:
 - Multiple IP Subnet
 - Custom DHCP Options
 - Bind-IP-to-MAC DHCP Pool Count up to 1022 addresses for LANs 1-3
 - DHCP Pool Count up to 253 addresses for LANs 4-8
- LAN IP Alias
- Wired 802.1x Port Authentication
- Port Mirroring
- Local DNS Server
- Conditional DNS Forwarding
- Hotspot Web Portal
 Hotspot Authentication: Click-Through, Social Login, SMS PIN, Voucher PIN, RADIUS, External Portal Server

- Networking Features
 Policy-based Routing: Protocol, IP Address, Port, Domain/Hostname,
- High Availability: Active-Standby, Hot-Standby DNS Security (DNSSEC)
- Local RADIUS server

- SMB File Sharing (Requires external storage)
 Multicast: IGMP Proxy, IGMP Snooping & Fast Leave, Bonjour
 Routing Features: IPv4 & IPv6 Static Routing, Inter-VLAN Routing, RIP v1/v2/ng, BGP

- VPN Features
 Up to 32 active VPN tunnels including up to 16 SSL VPN or OpenVPN
- Up to 16 Hardware Accelerated 800Mb/s IPsec tunnels New!
- LAN-to-LAN Dial-In VPN Server & Dial-Out VPN Client
- Teleworker-to-LAN Dial-In VPN Server
- User Authentication: Local, RADIUS, LDAP, TACACS+, mOTP IKE Authentication: Pre-Shared Key and Digital Signature (X.509) Encryption: MPPE, DES, 3DES, AES (128/192/256) Authentication: SHA-256, SHA-1 VPN Trunk (Redundancy): Load Balancing, Failover

- Dead Peer Detection (DPD)
- | IPsec NAT-Traversal (NAT-T) | Virtual IP Mapping Resolve VPN IP subnet/range conflicts
- DHCP over IPsec
- DrayTek VPN Matcher Connect to a VPN router that's behind NAT/ CG-NAT **New!**
- VPN Protocols:
 - IPsec IKEv1, IKEv2, IKEv2 EAP
 - IPsec-XAuth DrayTek SSL VPN
 - OpenVPN
 - GRE over IPsec

 - L2TP, L2TP over IPsec

Bandwidth Management • IP-based Bandwidth Limit

- IP-based Session Limit
- User-based Data Quota
- OoS (Quality of Service):
 Classify via TOS, DSCP, 802.1p, IP Address, Service Type
 4 Priority Queues
 App QoS

 - VolP Prioritization

- VoIP Features ('Vac' model)

 2x RJ-11 PSTN Telephone Ports (FXS)

 Integrated VoIP SIP ATA (Analogue Telephone Adapter)

 6 SIP Accounts with VoIP Setup Wizard

 Protocols: SIP, RTP / RTCP

- Voice Codecs: G.711 A / Law, G.723.1, G.726, G.729 A / B, VAD / CNG
 Tone Generation: DTMF, Dial, Busy, Ring Back, Call Progress
 DTMF Transmission: In Band, Out Band (RFC-2833), SIP info

- FAX / Modem Support with G.711 Pass-through and T.38
 Supplemental Services: Caller ID, Call Hold/Retrieve, Waiting, Transfer, Forwarding, Barring



Technical Specification (UK Hardware Spec.)

- DND (Do not Disturb)
- MWI (Message Waiting Indicator) (RFC-3842)
- Hotline (Dial preset number when handset lifted)

Management

- Local Service: HTTP, HTTPS, Telnet, SSH, FTP, TR-069

- Config File Export & Import
 Import Config from Vigor 2862
 Auto Backup Config to USB Storage New!
 Firmware Upgrade via TFTP, HTTP, TR-069
- 2-Level Administration Privilege
- Access Control Features: Access List, Brute Force Protection
- Syslog SMS, E-mail Notification Alert
- SNMP: v1, v2c, v3
- Managed by VigorACS
 Router Central Management Features:

 - AP Management: Up to 20 VigorAP access points
 Switch Management: Up to 10 VigorSwitch network switches
 VPN Management: Up to 8 Vigor routers
 DrayTek Mesh: Up to 7 VigorAP access points New! (requires f/w 4.3.0)

Operating Requirements

- rating Requirements
 Rack Mountable (Optional Vigor RM1 mounting bracket required)
 Wall or Shelf Mountable with included fittings
 Temperature Operating: 0 °C ~ 45 °C
 Storage: -25 °C ~ 70 °C
 Humidity 10% ~ 90% (non-condensing)
 Power Consumption: 28.2 watts maximum ('ax' model)
 Weight: 620g ('ax' model)
 Dimensions

- Dimensions`
 - 241mm Width
 - 165mm Depth
 - 44mm Height
- Operating Power: DC 12V (via external PSU, supplied) Warranty : Two (2) Years RTB Power Requirements : 100-240VAC

Box Contents

- Vigor 2865 series router
- Quick Start Guide
- Screws & wall plugs for wall mounting
- 2m Cat-5e RJ-45 Network Cable
- 2x Detachable Wireless LAN Antennas ('ac' & 'ax' models)
- 2x Detachable LTE Antennas ('L' models) 2x 1m LTE Extension Base ('L' models) DC 12V Power Supply with UK Plug

Vigor 2865 series Router Models

UK Product code	EAN	Product name	Product description
V2865-K	4710484741257	Vigor 2865 (UK/IE)	Vigor 2865 wired router
V2865AC-K	4710484741240	Vigor 2865ac (UK/IE)	Vigor 2865ac router with 11ac AC1300 wireless
V2865AX-K	4710484743862	Vigor 2865ax (UK/IE)	Vigor 2865ax VDSL router with Wi-Fi 6 AX3000 wireless
V2865LAC-K	4710484741233	Vigor 2865Lac (UK/IE)	Vigor 2865Lac router with 11ac AC1300 wireless and integrated 4G/LTE modem
V2865VAC-K	4710484743206	Vigor 2865Vac (UK/IE)	Vigor 2865Vac AC1300 wireless VDSL router with VoIP